



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : F03D 1/06	A1	(11) International Publication Number: WO 99/14490 (43) International Publication Date: 25 March 1999 (25.03.99)
(21) International Application Number: PCT/DK98/00378 (22) International Filing Date: 4 September 1998 (04.09.98) (30) Priority Data: 1009/97 4 September 1997 (04.09.97) DK (71) Applicant (for all designated States except US): LM GLAS-FIBER A/S [DK/DK]; Rolles Møllevej 1, DK-6640 Lunderskov (DK). (72) Inventors; and (75) Inventors/Applicants (for US only): ANDERSEN, Søren [DK/DK]; Gl. Møllevej 16, DK-6640 Lunderskov (DK). ALBERTSEN, Henrik [DK/DK]; Storegade 33, DK-6640 Lunderskov (DK). GRABAU, Peter [DK/DK]; H.C. Petersensvej 10, DK-6000 Kolding (DK). (74) Agent: K. SKØTT-JENSEN PATENTINGENIØRER A/S; Lemmingvej 225, DK-8361 Hasselager (DK).		(81) Designated States: AL, AM, AT, AT (Utility model), AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, CZ (Utility model), DE, DE (Utility model), DK, DK (Utility model), EE, EE (Utility model), ES, FI, FI (Utility model), GB, GE, GH, GM, HR, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (Utility model), SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>In English translation (filed in Danish).</i>

(54) Title: WINDMILL ROTOR AND WIND BLADES THEREFOR

(57) Abstract

With conventional windmills the wing blades used have a certain resilient flexibility which, in connection with "front runners", implies that the wings in strong wind are bent inwardly towards the mill tower, i.e. the wing rotor should be placed with a required safety spacing from the mill tower. An associated forward displacement of the entire rotor involves high costs and has already been avoided in various unsuccessful manners. The invention provides for an improved solution of the problem in disclosing that the wing blades, per se, are designated with such a forwardly curved configuration that the wing tips, when the wings are mounted in a conventional manner on the wing hub, will be located with increased spacing from the side of the tower.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Windmill rotor and wing blades therefor

The present invention concerns a windmill with a rotor of the usual type which is normally configured with three blades
5 extending from a blade hub on the main shaft of the windmill housing. The mill housing is disposed in a rotatable manner on the top of the mill tower, and with so-called front-runners the system is arranged so that the rotation of the mill housing is controlled to maintain the blade rotor facing
10 towards the wind, i.e. so that the wind first hits the rotor and thereafter the tower.

The windmill blades are predominantly configured as steel constructions where efforts are made to keep these both as light and as rigid as practically possible, the result being
15 a compromise in that the blades are provided with considerable rigidity, but at the same time also a certain elastic resilience which will naturally manifest itself with blades of greater lengths, e.g. 15-30m. The wind pressure in against the blade rotor, where the blades turn their broad sides
20 against the wind, will thus give rise to an elastic rearwards flexing of the blades. With rotating blades, this situation is alleviated to a considerable degree by two different circumstances, i.e. partly that the centrifugal force which simultaneously arises on the blades seeks to straighten out the
25 blades, and partly that the blades, as a consequence of their movement transversely to the wind, are influenced by a wind direction which is not facing directly in towards the broad surface of the blades. However, there will still arise a wind component which seeks to force the blades rearwards.

30 The consequence of this related, elastic flexing rearwards by the blades, is that during their movement past the tower, the stronger the wind the closer the outer ends of the blades will come to the tower. Since the windmills shall preferably also be able to function effectively in strong winds,
35 it is thus necessary for the blade rotor, seen in the direction of the mill housing's main shaft, to be positioned so far forwards that the blades, during their rotation, at no time can be exposed to influence by the wind to such a degree

that they make contact with the tower with associated risk of serious accidents or direct damage. Various items of security equipment can be used for the braking of the rotor in strong winds, but in such cases it must be taken into consideration
5 that the more the rotor is braked, the more the effective wind pressure against the blades' broad sides is increased to a considerable degree.

The problem could naturally be solved by the blade rotor being positioned at great distance from the mill tower, but
10 for many reasons this is a very expensive solution. Consequently, attention is focused on the stiffness of the blades, precisely so that these can withstand a high wind pressure without the blade hub having to be disposed at some exaggerated distance from the vertical axis of the tower.

15 The blades are traditionally constructed as aerodynamic shell profile elements with a long, straight main beam extending out along the blade at its thickest area. This main beam is in itself particularly rigid precisely in the direction which is relevant here, which will be in the direction
20 of the beam's height, but on the basis discussed there can be reason to undertake closer considerations with regard to the relevant flexibility of the beam, i.e. with regard to extra stiffening.

Two different methods have hitherto been suggested for
25 the solving of the problem, though without either of these having made the provision that the main beam should be stiffened, i.e. firstly that the blade rotor is placed on a main shaft which slopes slightly upwards, and secondly that the blades are mounted in a forwardly-inclined manner, which solutions can be briefly commented on as follows:
30

When use is made of an upwardly-sloping main shaft, the whole of the rotor plane is tipped upwards/rearwards, so that in their rotational movement in the space above the tower, the blades can freely swing in over the contour of the underlying tower, while the passage of the blades below will take
35 place at increased distance from the tower. The mill can thus operate with a considerable free distance between the tips of the blades and the side of the tower, even though the blade

hub is positioned more or less close to the tower, in that the blades below will thus swing free of the tower even with strong rearwards deflection, while above they will obviously swing free of the tower, even though they are deflected rear-
5 wards completely in over it.

With this arrangement, the rotor plane will be inclined in relation to the vertical, and it has been ascertained that merely this condition in itself appears generally unattractive aesthetically, because for an immediate consideration it
10 is rather illogical. It is known that there exists a deep emotional engagement surrounding the sensible utilisation of the wind power, and the condition named here is enough in itself to have a misleading effect on the debate in this field.

The same applies with said second solution outlined
15 above, i.e. where although the blades rotate in the vertical plane, they assume a "cone" formation in the forwards direction, i.e. they are placed in such inclined retaining parts on the blade hub that they will not only be simply "radiating", but each also slightly forwardly inclined, so that in
20 their rotation they described a conical surface. It can also be achieved hereby that the blade hub can be situated at a more or less short distance from the shaft of the mill tower, while the blade tips in a blade rotor rotating in the vertical plane have, however, ample possibilities of being pressed
25 back without hereby colliding with the mill tower. However, this solution is relatively costly, the reason being that it is expensive to arrange the slightly inclined retaining parts on the blade hub, and to which can be added that also the resulting appearance of a conical blade rotor gives rise to ob-
30 jections from the point of view of aesthetical criteria.

While there is a strong case that the invention should be concerned with a further stiffening of the said main beam in order to obtain a picture of a blade rotor rotating in a vertical plane, with the invention there is introduced the modification that the use of said "straight" beams is omitted in
35 the construction of the blades, and use being made instead of "high-edge curving" main beams, without necessarily speculating further concerning the stiffness of these beams.

The blades in themselves will thus be able to appear as a right-angled extension out from the blade hub, which can more or less gradually go over into a curved extension, e.g. merely along the outer third of the blade, so that the blade tips stand at a greater distance from the tower. A rotor with blades shaped in this way has proved not only to be more effective for the considered objective, but also aesthetically acceptable, in that visually the curving outwards manifests itself very little. For example, it will be quite an attractive result if the blade hub can be placed a half a metre closer to the tower shaft, and an associated outwards curvature of a blade with a length in the order of 25m will be only slightly visible, namely when the inner, thicker length parts can be seen to work in a plane which appears natural to the observer.

Compared to blades with the said negative coning, the blades according to the invention will distinguish themselves partly in that the rotor hub can be built in a conventional manner, and partly that the hub will be not influenced by substantial bending forces originating from the effect of centrifugal force on the blades. With coned blades, a great part of the straightening-out of the blades will be due precisely to the centrifugal force, so that they must be extra coned in order also to accommodate the rearwards deflection which occurs under wind pressure.

Compared with the said tilted rotors, the invention offers the advantage that the blades are influenced in a uniform manner all the way around, in quite the same way as with conventional rotors, while the blades in a tilted rotor are influenced unevenly, i.e. all depending on whether they are moving upwards or downwards, and are consequently herewith moving respectively with and against the wind, which corresponds to a yawing-error which can give rise to various problems.

As mentioned above, it is characteristic of a blade according to the invention that the main beam itself is partly formed with a curvature in the high-edge plane, but it must be emphasized, however, that the invention is not limited to

this, in that by formation in a suitably shaped mould the blade can be given the desired curvature also with wholly or partly beam-free box constructions.

The invention will now be described in more detail with
5 reference to the drawing, in which

Fig. 1 shows a windmill with a blade rotor according to the invention seen from the side,

Fig. 2 shows a windmill blade seen from the front, and

Fig. 3 shows the blade in Fig. 2 seen from the side edge.
10

The windmill shown in Fig. 1 consists in the normal manner of a tower 2, a mill housing 4 and a main shaft 6 with rotor hub 8 for blades 10 which constitutes a blade rotor. The mill is a "front-runner", where the rotor turns forwards
15 towards the wind W, which means that the wind pressure will bend the blades backwards and herewith inwards towards the tower 2. Therefore, the system 4,6 must be disposed in such a manner that the necessary safety distance must exist between the blades 10 and the tower.

20 With the invention, this distance can be minimized by the blades being provided with a forwardly-directed curvature, preferably only over an outer extent 12, whereby the tips of the blades, when at rest, will stand at some distance (a) in front of the plane p which is formed by the blade axes at the
25 root parts of the blades. The blades can hereby be constructed so that also in strong winds they will lie at a safe distance outside the tower, possibly curving slightly rearwards towards.

In Fig. 2 and 3 is shown an authentic configuration of a
30 windmill blade with a length of 29m. The outwards curvature of the tip shown in Fig. 3 amounts to approximately 50cm, but this may well be somewhat larger or somewhat smaller. However, it is preferable that the curvature is not much greater than the radius of the blade root, since this can give rise
35 to certain difficulties in the transport of the blade.

The invention does not prescribe in detail the conditions for how and with what curvature the curvature should be produced, in that this must be determined on a professional

level while paying regard to the blade construction in general. Consequently, it shall not be excluded that it can be chosen to place the curvature almost as a bend in the thick end part of the blade, with the outer part of the blade extending straight or slightly curved.

It must be mentioned that in the claims it has been chosen to relate the invention to the said coned rotors as known technique, and that it has hereby been found expedient to refer to the blade axes p as centre of the normally cylindrical-shaped blade root parts where these are secured to the blade hub or at their transition area to the hub.

C L A I M S

1. Windmill rotor of the kind where the windmill blades extend outwards from a securing or transition area at a rotor hub to a tip area which lies at a distance in front of the normal plane of the rotor hub through the blade axes' intersection points with the hub circumference, c h a r a c-
5 t e r i z e d in that the blades extend outwards from the hub in said normal plane, and at a distance from the hub then extend in an outwardly/forwardly, curving manner.
10

2. Windmill blade for a rotor according to claim 1, c h a r a c t e r i z e d in that in the free condition the blade extends in a forwardly-curved manner in the transverse plane of the blade over a length at a distance from the blade
15 root.

3. Windmill blade according to claim 2, c h a r a c-
t e r i z e d in that the curvature results in a forwards disposition of the blade tip of a magnitude corresponding to the radius of the root part of the blade.

1/1





Fig. 2

Fig. 3



INTERNATIONAL SEARCH REPORT

International application No.

PCT/DK 98/00378

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: F03D 1/06

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: F03D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,N0 classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4550259 A (BERTELS), 29 October 1985 (29.10.85), figure 4 -- -----	1-3

☐

Further documents are listed in the continuation of Box C.

☒

See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

7 December 1998

Date of mailing of the international search report

10 -12- 1998

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM

Authorized officer

Jan-Axel Ylivainio

Information on patent family members

International application No.

PCT/DK 98/00378

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 4550259 A	29/10/85	AU 1725083 A	31/01/85
		DK 326583 A	29/01/84
		EP 0102657 A	14/03/84
		JP 59041679 A	07/03/84
		NL 8203019 A	16/02/84
